

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2310D

SIMOTICS SD - 315 S - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	60	57.42	-/-	113.00	890	616.1	93.3	93.3	92.7	0.79	0.73	0.60	6.4	2.3	2.9	IE2
690	Y	60	57.42	-/-	65.00	890	616.1	93.3	93.3	92.7	0.79	0.73	0.60	6.4	2.3	2.9	IE2
400	Δ	60	55.00	-/-	108.00	890	590.0	93.0	93.0	92.1	0.79	0.73	0.61	6.6	2.4	2.9	IE2
690	Y	60	55.00	-/-	63.00	890	590.0	93.0	93.0	92.1	0.79	0.73	0.61	6.6	2.4	2.9	IE2
IM B3 / IM 1001		FS 315 S		640 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +55 °C / 1,000 m

Locked rotor time (hot / cold) : 21.7 s | 35.2 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69.0 / 83.0 dB(A) ²⁾	72.0 / 86.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	2.0000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g	3000 h	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(A) without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5
Contact screw thread	M12	Cable gland	2 plugs


Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status		customer	
	datasheet	released			
	title	document number			
	1LE1501-3AD03-1AA4-Z				
	N07	rev.	creation date	language	Page
© Siemens AG 2021		01	2021-04-23 08:33	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2310D

SIMOTICS SD - 315 S - IM B3 - 8p

Special design

N07 Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1501-3AD03-1AA4-Z				document number			
© Siemens AG 2021	N07				rev. 01	creation date 2021-04-23 08:33	language en	Page 2/2