

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1184B

SIMOTICS SD - 180 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
400	Δ	50	22.00	-/-	42.50	1465	143.0	89.9	90.8	90.7	0.83	0.78	0.67	8.0	2.7	3.6	IE1
690	Y	50	22.00	-/-	24.50	1465	143.0	89.9	90.8	90.7	0.83	0.78	0.67	8.0	2.7	3.6	IE1
460	Δ	60	25.30	-/-	41.50	1765	137.0	91.0	91.7	91.5	0.84	0.79	0.69	8.2	2.7	3.6	IE1
IM B5 / IM 3001		FS 180 L		170 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 7.76 s | 14 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75.0 / 79.0 dB(A) ²⁾	75.0 / 79.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.1300 kg m ²		Vibration severity grade	A
Bearing DE NDE	NU 210	6210 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1502-1EB43-4FF4-Z D22+F70+G11+L22			document number				
© Siemens AG 2021				rev. 01	creation date 2021-04-21 13:24	language en	Page 1/2	

SIMOTICS SD - 180 L - IM B5 - 4p

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	G11	Rotary pulse encoder Sendix 5020 (HTL)
F70	Mounting of separately driven fan	L22	Bearing design for increased cantilever forces

--

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer	
	title 1LE1502-1EB43-4FF4-Z			document number			
© Siemens AG 2021	D22+F70+G11+L22			rev. 01	creation date 2021-04-21 13:24	language en	Page 2/2