

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1220B

SIMOTICS SD - 225 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
230	Δ	50	37.00	-/-	120.00	1475	240.0	91.2	91.6	91.1	0.85	0.81	0.71	7.0	2.3	3.2	IE1
400	Y	50	37.00	-/-	69.00	1475	240.0	91.2	91.6	91.1	0.85	0.81	0.71	7.0	2.3	3.2	IE1
460	Y	60	42.50	-/-	67.00	1775	230.0	93.0	93.3	92.5	0.86	0.83	0.74	7.0	2.3	3.2	IE1
IM B3 / IM 1001		FS 225 S		260 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 13.1 s | 22.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	72.4 / 86.0 dB(A) ²⁾	76.4 / 90.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.3700 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator						
	document type			document status		customer		
	datasheet			released				
© Siemens AG 2021	title			document number				
	1LE1502-2BB02-2AF4-Z							
	B02+D22+D47+F70+G11+R12+Y53+Y84			rev.	creation date	language	Page	
				01	2021-04-22 15:48	en	1/2	

SIMOTICS SD - 225 S - IM B3 - 4p

B02	Acceptance test certificate 3.1 acc. to EN 10204	G11	Rotary pulse encoder Sendix 5020 (HTL)
D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	R12	Terminal box rotated through 180°
D47	TR CU product safety certificate EAC for the Eurasian Customs Union	Y53	Paint finish in other standard RAL colours
F70	Mounting of separately driven fan	Y84	Additional data on the rating plate and on the packing label :

Notes:

responsible dep. DI MC LVM		technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
		document type datasheet			document status released		customer	
		title 1LE1502-2BB02-2AF4-Z			document number			
© Siemens AG 2021		B02+D22+D47+F70+G11+R12+Y53+Y84			rev. 01	creation date 2021-04-22 15:48	language en	Page 2/2