

SIMOTICS SD - 225 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
400	Δ	50	37.00	-/-	69.00	1475	240.0	91.2	91.6	91.1	0.85	0.81	0.71	7.0	2.3	3.2	IE1
690	Y	50	37.00	-/-	40.00	1475	240.0	91.2	91.6	91.1	0.85	0.81	0.71	7.0	2.3	3.2	IE1
460	Δ	60	42.50	-/-	67.00	1775	230.0	93.0	93.3	92.5	0.86	0.83	0.74	7.0	2.3	3.2	IE1
IM B3 / IM 1001			FS 225 S		260 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 13.1 s | 22.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	68.0 / 82.0 dB(A) ²⁾	72.0 / 86.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.3700 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(C) 6 PTC thermistors - for alarm and tripping (4 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1502-2BB03-4AC4-Z			document number				
	© Siemens AG 2021	D22+D47			rev. 01	creation date 2021-04-22 19:34	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1220B

SIMOTICS SD - 225 S - IM B3 - 4p

Special design

D22 motor without CE character for export outside the EEA (see EU regulation 640/2009) D47 TR CU product safety certificate EAC for the Eurasian Customs Union

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1502-2BB03-4AC4-Z				document number			
© Siemens AG 2021	D22+D47				rev. 01	creation date 2021-04-22 19:34	language en	Page 2/2