

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1222B

SIMOTICS SD - 225 M - IM B3 - 4p

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

Remarks

Electrical data

Safe Area

| U               | Δ / Y | f        | P     | P      | I     | n       | M     | η <sup>3)</sup> |      |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-----------------|-------|----------|-------|--------|-------|---------|-------|-----------------|------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]             |       | [Hz]     | [kW]  | [hp]   | [A]   | [1/min] | [Nm]  | 4/4             | 3/4  | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| 400             | Δ     | 50       | 45.00 | -/-    | 82.00 | 1475    | 290.0 | 91.7            | 92.1 | 91.7                   | 0.86               | 0.83 | 0.74 | 7.2                            | 2.6                            | 3.2                            | IE1   |
| 690             | Y     | 50       | 45.00 | -/-    | 47.50 | 1475    | 290.0 | 91.7            | 92.1 | 91.7                   | 0.86               | 0.83 | 0.74 | 7.2                            | 2.6                            | 3.2                            | IE1   |
| 460             | Δ     | 60       | 52.00 | -/-    | 81.00 | 1770    | 280.0 | 93.0            | 93.4 | 92.9                   | 0.87               | 0.84 | 0.77 | 7.2                            | 2.6                            | 3.2                            | IE1   |
|                 |       |          |       |        |       |         |       |                 |      |                        |                    |      |      |                                |                                |                                |       |
| IM B3 / IM 1001 |       | FS 225 M |       | 290 kg |       | IP55    |       | IEC/EN 60034    |      | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 13.5 s | 23.3 s

Mechanical data

|                                                                                     |                                 |                                 |                            |                                         |
|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------|----------------------------|-----------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 71.0 / 82.0 dB(A) <sup>2)</sup> | 74.0 / 86.0 dB(A) <sup>2)</sup> | External earthing terminal | Yes (standard)                          |
| Moment of inertia                                                                   | 0.4500 kg m <sup>2</sup>        |                                 | Vibration severity grade   | A                                       |
| Bearing DE   NDE                                                                    | 6213 Z C3                       | 6213 Z C3                       | Insulation                 | 155(F) to 130(B)                        |
| bearing lifetime                                                                    |                                 |                                 | Duty type                  | S1                                      |
| L <sub>10mh</sub> F <sub>Rad min</sub> 50 60Hz <sup>1)</sup> for coupling operation | 40000 h                         | 32000 h                         | Direction of rotation      | bidirectional                           |
| Lubricants                                                                          | Unirex N3                       |                                 | Frame material             | cast iron                               |
| Regreasing device                                                                   | No                              |                                 | Coating (paint finish)     | Standard paint finish C2                |
| Grease nipple                                                                       | -/-                             |                                 | Color, paint shade         | RAL7030                                 |
| Type of bearing                                                                     | Locating bearing NDE            |                                 | Motor protection           | (A) without (Standard)                  |
| Condensate drainage holes                                                           | Yes (standard)                  |                                 | Method of cooling          | IC411 - self ventilated, surface cooled |

Terminal box

|                          |           |                                |                      |
|--------------------------|-----------|--------------------------------|----------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 35.0 mm <sup>2</sup> |
| Material of terminal box | cast iron | Cable diameter from ... to ... | 27.0 mm - 35.0 mm    |
| Type of terminal box     | TB1 L01   | Cable entry                    | 2xM50x1,5            |
| Contact screw thread     | M8        | Cable gland                    | 2 plugs              |

Notes:

|                                                                         |                                           |                                                                  |
|-------------------------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| I <sub>A</sub> /I <sub>N</sub> = locked rotor current / current nominal | 1) L10mh according to DIN ISO 281 10/2010 | 3) Value is valid only for DOL operation with motor design IC411 |
| M <sub>K</sub> /M <sub>N</sub> = locked rotor torque / torque nominal   | 2) at rated power / at full load          |                                                                  |
| M <sub>B</sub> /M <sub>N</sub> = break down torque / nominal torque     |                                           |                                                                  |

|                                                                                    |                      |                 |             |                                                                                                              |                  |          |      |
|------------------------------------------------------------------------------------|----------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|------------------|----------|------|
| responsible dep.                                                                   | technical reference  | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                  |          |      |
| DI MC LVM                                                                          |                      | DT Configurator |             |                                                                                                              |                  |          |      |
|  | document type        |                 |             | document status                                                                                              |                  | customer |      |
|                                                                                    | datasheet            |                 |             | released                                                                                                     |                  |          |      |
|                                                                                    | title                |                 |             | document number                                                                                              |                  |          |      |
|                                                                                    | 1LE1502-2BB23-4AA4-Z |                 |             |                                                                                                              |                  |          |      |
|                                                                                    | D22                  |                 |             | rev.                                                                                                         | creation date    | language | Page |
| © Siemens AG 2021                                                                  |                      |                 |             | 01                                                                                                           | 2021-04-23 13:40 | en       | 1/2  |

## Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1222B

SIMOTICS SD - 225 M - IM B3 - 4p

### Special design

D22 motor without CE character for export outside the EEA (see EU regulation 640/2009)

### Notes:

|                                                                                    |                               |                               |                                   |  |                                                                                                              |             |  |  |
|------------------------------------------------------------------------------------|-------------------------------|-------------------------------|-----------------------------------|--|--------------------------------------------------------------------------------------------------------------|-------------|--|--|
| responsible dep.<br>DI MC LVM                                                      | technical reference           | created by<br>DT Configurator | approved by                       |  | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |             |  |  |
|  | document type<br>datasheet    | document status<br>released   |                                   |  | customer                                                                                                     |             |  |  |
|                                                                                    | title<br>1LE1502-2BB23-4AA4-Z |                               |                                   |  |                                                                                                              |             |  |  |
| © Siemens AG 2021                                                                  | D22                           | rev.<br>01                    | creation date<br>2021-04-23 13:40 |  | language<br>en                                                                                               | Page<br>2/2 |  |  |