

SIMOTICS SD - 250 M - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
380	Δ	50	55.00	-/-	103.00	2970	177.0	92.1	92.1	91.2	0.88	0.86	0.79	6.7	2.1	3.0	IE1
660	Y	50	55.00	-/-	59.00	2970	177.0	92.1	92.1	91.2	0.88	0.86	0.79	6.7	2.1	3.0	IE1
440	Δ	60	62.00	-/-	99.00	3570	166.0	92.4	92.2	91.0	0.89	0.87	0.81	6.7	2.0	2.9	IE1
IM B5 / IM 3001			FS 250 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 16.8 s 30.9 s								

Sound level (SPL / SWL) at 50Hz 60Hz	76 / 90 dB(A) ^{2) 3)}	81 / 94 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.4000 kg m ²		Thermal class	F
Bearing DE NDE	6215 Z C3	6215 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	360 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	120 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_r/I_n = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_n = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_n = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1LE1502-2CA23-3FB4-Z			document number			
© Siemens AG 2023	D22+D47			rev. 943	creation date 2023-03-28	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1252A

SIMOTICS SD - 250 M - IM B5 - 2p

Special design

D22	Motor without CE character for export outside the EEA (see EU regulation 2019/1781)	D47	TR CU product safety certificate EAC for the Eurasian Customs Union
-----	---	-----	---

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
	document type datasheet				document status released			
	title 1LE1502-2CA23-3FB4-Z				document number			
© Siemens AG 2023	D22+D47				rev. 943	creation date 2023-03-28		language en