

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1310B

SIMOTICS SD - 315 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
380	Δ	50	110.00	-/-	215.00	1488	710.0	93.3	93.4	92.8	0.84	0.80	0.71	6.5	2.3	2.7	IE1
660	Y	50	110.00	-/-	123.00	1488	710.0	93.3	93.4	92.8	0.84	0.80	0.71	6.5	2.3	2.7	IE1
440	Δ	60	127.00	-/-	210.00	1788	680.0	93.5	93.5	92.6	0.85	0.82	0.74	6.5	2.3	2.7	IE1
IM B3 / IM 1001		FS 315 S		730 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 20.9 s | 39.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	72.9 / 87.3 dB(A) ²⁾	76.7 / 91.1 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	1.9000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC416 - separately ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_A/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
SIEMENS	document type	datasheet		document status		released	
	title	1LE1502-3AB03-3AF4-Z		document number			
© Siemens AG 2021		D22+F70+G41		rev.	creation date	language	Page
				01	2021-04-23 15:24	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1310B

SIMOTICS SD - 315 S - IM B3 - 4p

Special design

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	G41	Prepared to mount components with D12 shaft
F70	Mounting of separately driven fan		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
SIEMENS	document type datasheet			document status released		customer		
	title 1LE1502-3AB03-3AF4-Z			document number				
© Siemens AG 2021	D22+F70+G41			rev. 01	creation date 2021-04-23 15:24	language en	Page 2/2	