

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1314B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cosφ ³⁾			I _A /I _N I _i /I _N	M _A /M _N T _i /T _N	M _K /M _N T _B /T _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
IM B3 / IM 1001			FS 315 L		940 kg		IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 37.2 s 37.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	76.0 / 90.0 dB(A) ²⁾	75.0 / 89.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	2.9000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(C) 6 PTC thermistors - for alarm and tripping (4 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	right	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1502-3AB49-0AC5-Z B02+H07+M1Y+Q01+Q02+R62			document number				
© Siemens AG 2021				rev. 01	creation date 2021-04-20 21:33	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1314B

SIMOTICS SD - 315 L - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings
H07	Stainless steel screws and bolts (outside the motor)	Q02	Anti-condensation heating for 230 V (2 terminals)
M1Y	Non-standard winding:	R62	Cast iron auxiliary terminal box (small)

Additional information:

Space heaters

Technical data: 1-phase, 230 V 109W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1502-3AB49-0AC5-Z B02+H07+M1Y+Q01+Q02+R62				document number			
© Siemens AG 2021			rev. 01	creation date 2021-04-20 21:33		language en	Page 2/2	