

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3094B

SIMOTICS SD - 90 L - IM B34 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	1.38	-/-	5.20	1445	9.1	85.4	85.4	83.6	0.78	0.70	0.56	7.9	3.1	3.8	IE3
400	Y	50	1.38	-/-	3.00	1445	9.1	85.4	85.4	83.6	0.78	0.70	0.56	7.9	3.1	3.8	IE3
460	Y	60	1.61	-/-	3.00	1740	8.8	86.6	86.4	84.6	0.78	0.71	0.58	8.4	3.1	4.0	IE3
460	Y	60	1.50	-/-	2.85	1755	8.2	86.5	86.6	84.7	0.77	0.69	0.57	8.6	3.4	4.3	IE3
IM B34 / IM 2101		FS 90 L				IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 17.3 s | 21.5 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	56 / 68 dB(A) ^{2) 3)}	58 / 70 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0049 kg m ²		Thermal class	F
Bearing DE NDE	6205 2Z C3	6204 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	31 kg
Regreasing device	No		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 D01	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1503-0EB42-2NA4-Z B07+H03+N06+P01+R12+S02+Y53+Y58				
© Siemens AG 2022		rev.	creation date	language	Page
		01	2022-08-31	en	1/2



Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3094B

SIMOTICS SD - 90 L - IM B34 - 4p

Special design

B07	Supplementary plate, voltage tolerance	R12	Terminal box rotated through 180°
H03	Condensation drain holes in end shield	S02	Special paint finish C3
N06	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 50°C, power reduced	Y53	Paint finish in other standard RAL colours
P01	Next larger standard flange	Y58	Non-standard cylindrical shaft extension, DE

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE1503-0EB42-2NA4-Z B07+H03+N06+P01+R12+S02+Y53+Y58			document number			
© Siemens AG 2022				rev. 01	creation date 2022-08-31	language en	Page 2/2