

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3090C

SIMOTICS SD - 90 S - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
230	Δ	50	0.75	-/-	3.40	945	7.6	78.9	80.0	78.8	0.70	0.62	0.50	4.6	2.2	2.6	IE3
400	Y	50	0.75	-/-	1.96	945	7.6	78.9	80.0	78.8	0.70	0.62	0.50	4.6	2.2	2.6	IE3
460	Y	60	0.86	-/-	1.87	1140	7.2	82.5	83.2	81.7	0.70	0.62	0.50	4.9	2.1	2.7	IE3
460	Y	60	0.75	-/-	1.76	1155	6.2	82.5	82.4	79.9	0.65	0.56	0.44	5.3	2.4	3.1	IE3

IM B3 / IM 1001	FS 90 S	26 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	---------	-------	------	--------------	------------------------

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 40.4 s | 50.1 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	43.0 / 55.0 dB(A) ²⁾	46.0 / 58.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0040 kg m ²		Vibration severity grade	A
Bearing DE NDE	6205 2Z C3	6204 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 D01	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1503-0EC02-2AA4			
© Siemens AG 2021	rev.	creation date	language	Page
	01	2021-04-22 00:38	en	1/1