

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3105B

SIMOTICS SD - 100 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	3.00	-/-	10.30	1460	19.6	87.7	88.4	88.2	0.83	0.78	0.69	7.3	2.3	3.7	IE3
400	Y	50	3.00	-/-	5.90	1460	19.6	87.7	88.4	88.2	0.83	0.78	0.69	7.3	2.3	3.7	IE3
460	Y	60	3.45	-/-	5.80	1760	18.7	89.5	90.1	89.4	0.84	0.79	0.68	7.6	2.2	3.8	IE3
460	Y	60	3.00	-/-	5.20	1765	16.2	89.5	89.6	88.9	0.81	0.76	0.68	8.6	2.6	4.3	IE3
IM B3 / IM 1001		FS 100 L		40 kg		IP65		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - + °C / 1,000 m

Locked rotor time (hot / cold) : 13.9 s | 18.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 72.0 dB(A) ²⁾	62.0 / 74.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0140 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F01	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status		customer	
				released			
	title	1LE1503-1AB52-2AA4-Z		document number			
© Siemens AG 2021	H20+N03			rev.	creation date	language	Page
	01			2021-04-21 22:58	en	1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3105B

SIMOTICS SD - 100 L - IM B3 - 4p

Special design

H20	IP 65 degree of protection	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature
-----	----------------------------	-----	---

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
-------------------------------	---------------------	-------------------------------	-------------	--

	document type	document status		customer	
	datasheet	released			
	title	document number			
	1LE1503-1AB52-2AA4-Z				
	H20+N03	rev.	creation date	language	Page
© Siemens AG 2021		01	2021-04-21 22:58	en	2/2