

SIMOTICS SD - 132 S - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	7.50	-/-	13.10	2950	24.5	90.1	91.0	91.0	0.92	0.90	0.84	8.3	1.9	3.9	IE3
690	Y	50	7.50	-/-	7.60	2950	24.5	90.1	91.0	91.0	0.92	0.90	0.84	8.3	1.9	3.9	IE3
460	Δ	60	8.60	-/-	13.00	3550	23.0	90.2	90.8	90.5	0.92	0.90	0.84	8.2	2.0	3.9	IE3
460	Δ	60	7.50	-/-	11.50	3560	20.0	90.2	90.4	89.6	0.91	0.88	0.82	9.4	2.2	4.5	IE3
IM B5 / IM 3001			FS 132 S			IP65	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 9.3 s 13.6 s								

Sound level (SPL / SWL) at 50Hz 60Hz	68 / 80 dB(A) ^{2) 3)}	72 / 84 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0310 kg m²		Thermal class	F
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	73 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H01	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_{Lr}/I_{Ln} = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_{rn} = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_{bn} = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1503-1CA13-4FB4-Z						
	H20			rev.	creation date	language	Page
© Siemens AG 2023				942	2023-03-01	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3131A

SIMOTICS SD - 132 S - IM B5 - 2p

Special design

H20 IP 65 degree of protection

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE1503-1CA13-4FB4-Z			document number			
© Siemens AG 2023	H20			rev. 942	creation date 2023-03-01	language en	Page 2/2