

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3132B

SIMOTICS SD - 132 M - IM B3 - 4p

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

Remarks

Electrical data

Safe Area

| U               | Δ / Y | f        | P    | P     | I     | n       | M    | η <sup>3)</sup> |      |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-----------------|-------|----------|------|-------|-------|---------|------|-----------------|------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]             |       | [Hz]     | [kW] | [hp]  | [A]   | [1/min] | [Nm] | 4/4             | 3/4  | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| 230             | Δ     | 50       | 7.50 | -/-   | 25.00 | 1470    | 48.5 | 90.4            | 91.1 | 90.8                   | 0.84               | 0.80 | 0.71 | 7.4                            | 2.4                            | 3.5                            | IE3   |
| 400             | Y     | 50       | 7.50 | -/-   | 14.30 | 1470    | 48.5 | 90.4            | 91.1 | 90.8                   | 0.84               | 0.80 | 0.71 | 7.4                            | 2.4                            | 3.5                            | IE3   |
| 460             | Y     | 60       | 8.60 | -/-   | 14.20 | 1770    | 46.5 | 89.5            | 90.0 | 89.5                   | 0.85               | 0.81 | 0.73 | 7.5                            | 2.1                            | 3.5                            | IE2   |
| 460             | Y     | 60       | 7.50 | -/-   | 12.70 | 1775    | 40.5 | 89.5            | 89.6 | 88.6                   | 0.83               | 0.79 | 0.69 | 8.5                            | 2.4                            | 4.0                            | IE2   |
| IM B3 / IM 1001 |       | FS 132 M |      | 80 kg |       | IP55    |      | IEC/EN 60034    |      | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 15.6 s | 22 s

Mechanical data

|                                                                                     |                                 |                                 |                            |                                         |
|-------------------------------------------------------------------------------------|---------------------------------|---------------------------------|----------------------------|-----------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 64.0 / 76.0 dB(A) <sup>2)</sup> | 68.0 / 80.0 dB(A) <sup>2)</sup> | External earthing terminal | No                                      |
| Moment of inertia                                                                   | 0.0460 kg m <sup>2</sup>        |                                 | Vibration severity grade   | A                                       |
| Bearing DE   NDE                                                                    | 6208 2Z C3                      | 6208 2Z C3                      | Insulation                 | 155(F) to 130(B)                        |
| bearing lifetime                                                                    |                                 |                                 | Duty type                  | S1                                      |
| L <sub>10mh</sub> F <sub>Rad min</sub> 50 60Hz <sup>1)</sup> for coupling operation | 40000 h                         | 32000 h                         | Direction of rotation      | bidirectional                           |
| Lubricants                                                                          | Unirex N3                       |                                 | Frame material             | cast iron                               |
| Regreasing device                                                                   | No                              |                                 | Coating (paint finish)     | Standard paint finish C2                |
| Grease nipple                                                                       | -/-                             |                                 | Color, paint shade         | RAL7030                                 |
| Type of bearing                                                                     | Preloaded bearing DE            |                                 | Motor protection           | (A) without (Standard)                  |
| Condensate drainage holes                                                           | Yes (standard)                  |                                 | Method of cooling          | IC411 - self ventilated, surface cooled |

Terminal box

|                          |           |                                |                     |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 6.0 mm <sup>2</sup> |
| Material of terminal box | cast iron | Cable diameter from ... to ... | 11.0 mm - 21.0 mm   |
| Type of terminal box     | TB1 H01   | Cable entry                    | 2xM32x1,5           |
| Contact screw thread     | M4        | Cable gland                    | 2 plugs             |

Notes:

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal  
M<sub>K</sub>/M<sub>N</sub> = locked rotor torque / torque nominal  
M<sub>B</sub>/M<sub>N</sub> = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010  
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

|                                                                                    |                     |                 |             |                                                                                                              |                  |          |      |
|------------------------------------------------------------------------------------|---------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|------------------|----------|------|
| responsible dep.                                                                   | technical reference | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                  |          |      |
| DI MC LVM                                                                          |                     | DT Configurator |             |                                                                                                              |                  |          |      |
|  | document type       |                 |             | document status                                                                                              |                  | customer |      |
|                                                                                    | datasheet           |                 |             | released                                                                                                     |                  |          |      |
|                                                                                    | title               |                 |             | document number                                                                                              |                  |          |      |
|                                                                                    | 1LE1503-1CB22-2AA4  |                 |             |                                                                                                              |                  |          |      |
| © Siemens AG 2021                                                                  |                     |                 |             | rev.                                                                                                         | creation date    | language | Page |
|                                                                                    |                     |                 |             | 01                                                                                                           | 2021-04-22 00:49 | en       | 1/1  |