

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3132B

SIMOTICS SD - 132 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	7.50	-/-	14.30	1470	48.5	90.4	91.1	90.8	0.84	0.80	0.71	7.4	2.4	3.5	IE3
690	Y	50	7.50	-/-	8.30	1470	48.5	90.4	91.1	90.8	0.84	0.80	0.71	7.4	2.4	3.5	IE3
460	Δ	60	8.60	-/-	14.20	1770	46.5	89.5	90.0	89.5	0.85	0.81	0.73	7.5	2.1	3.5	IE2
460	Δ	60	7.50	-/-	12.70	1775	40.5	89.5	89.6	88.6	0.83	0.79	0.69	8.5	2.4	4.0	IE2
IM B3 / IM 1001		FS 132 M		80 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 15.6 s | 22 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64.0 / 76.0 dB(A) ²⁾	68.0 / 80.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0460 kg m ²		Vibration severity grade	A
Bearing DE NDE	6308 2Z C3	6208 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	6.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 H01	Cable entry	2xM32x1,5-1xM16x1,5
Contact screw thread	M4	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status		customer	
				released			
	title	1LE1503-1CB23-4AF4-Z		document number			
© Siemens AG 2021	G04+L22			rev.	creation date	language	Page
	01			2021-04-22 21:54	en	1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3132B

SIMOTICS SD - 132 M - IM B3 - 4p

Special design

G04 Mounted rotary pulse encoder LL 861 900 220 L22 Bearing design for increased cantilever forces

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1503-1CB23-4AF4-Z							
© Siemens AG 2021	G04+L22	rev. 01	creation date 2021-04-22 21:54		language en	Page 2/2		