

# Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3136B

SIMOTICS SD - 132 M - IM B3 - 4p

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

Remarks

## Electrical data

## Safe Area

| U                                                    | Δ / Y | f        | P     | P    | I     | n       | M    | η <sup>3)</sup> |                                                  |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|------------------------------------------------------|-------|----------|-------|------|-------|---------|------|-----------------|--------------------------------------------------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]                                                  |       | [Hz]     | [kW]  | [hp] | [A]   | [1/min] | [Nm] | 4/4             | 3/4                                              | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| DOL duty (S1) - 155(F) to 130(B)                     |       |          |       |      |       |         |      |                 |                                                  |                        |                    |      |      |                                |                                |                                |       |
| 380                                                  | Δ     | 50       | 11.00 | -/-  | 23.00 | 1470    | 71.0 | 91.4            | 91.8                                             | 91.1                   | 0.79               | 0.73 | 0.61 | 8.3                            | 2.8                            | 3.8                            | IE3   |
| 660                                                  | Y     | 50       | 11.00 | -/-  | 13.30 | 1470    | 71.0 | 91.4            | 91.8                                             | 91.1                   | 0.79               | 0.73 | 0.61 | 8.3                            | 2.8                            | 3.8                            | IE3   |
| 440                                                  | Δ     | 60       | 12.60 | -/-  | 22.00 | 1770    | 68.0 | 92.4            | 92.6                                             | 92.0                   | 0.81               | 0.76 | 0.65 | 8.8                            | 2.7                            | 3.8                            | IE3   |
| 440                                                  | Δ     | 60       | 11.00 | -/-  | 20.00 | 1775    | 59.0 | 92.4            | 92.0                                             | 91.0                   | 0.78               | 0.72 | 0.60 | 9.8                            | 3.1                            | 4.4                            | IE3   |
| IM B3 / IM 1001                                      |       | FS 132 M |       |      |       | IP55    | UKCA | IEC/EN 60034    |                                                  | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |
| Environmental conditions : -20 °C - +40 °C / 1,000 m |       |          |       |      |       |         |      |                 | Locked rotor time (hot / cold) : 14.4 s   20.6 s |                        |                    |      |      |                                |                                |                                |       |

## Mechanical data

|                                                                                     |                                |                                |                                 |                                         |
|-------------------------------------------------------------------------------------|--------------------------------|--------------------------------|---------------------------------|-----------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 64 / 78 dB(A) <sup>2) 3)</sup> | 69 / 82 dB(A) <sup>2) 3)</sup> | Vibration severity grade        | A                                       |
| Moment of inertia                                                                   | 0.0410 kg m <sup>2</sup>       |                                | Thermal class                   | F                                       |
| Bearing DE   NDE                                                                    | 6208 2Z C3                     | 6208 2Z C3                     | Duty type                       | S1                                      |
| bearing lifetime                                                                    |                                |                                | Direction of rotation           | bidirectional                           |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup> | 40000 h                        | 32000 h                        | Frame material                  | cast iron                               |
| Regreasing device                                                                   | No                             |                                | Net weight of the motor (IM B3) | 99 kg                                   |
| Grease nipple                                                                       | -/-                            |                                | Coating (paint finish)          | Standard paint finish C2                |
| Type of bearing                                                                     | Preloaded bearing DE           |                                | Color, paint shade              | RAL7030                                 |
| Condensate drainage holes                                                           | Yes (standard)                 |                                | Motor protection                | (A) without (Standard)                  |
| External earthing terminal                                                          | No                             |                                | Method of cooling               | IC411 - self ventilated, surface cooled |

## Terminal box

|                          |           |                                |                   |
|--------------------------|-----------|--------------------------------|-------------------|
| Terminal box position    | top       | Max. cross-sectional area      | 6 mm <sup>2</sup> |
| Material of terminal box | cast iron | Cable diameter from ... to ... | 11 mm - 21 mm     |
| Type of terminal box     | TB1 H01   | Cable entry                    | 2xM32x1,5         |
| Contact screw thread     | M4        | Cable gland                    | 2 plugs           |

## Notes:

|                                                                         |                                           |                                                                  |
|-------------------------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| I <sub>A</sub> /I <sub>N</sub> = locked rotor current / current nominal | 1) L10mh according to DIN ISO 281 10/2010 | 3) Value is valid only for DOL operation with motor design IC411 |
| M <sub>K</sub> /M <sub>N</sub> = locked rotor torque / torque nominal   | 2) at rated power / at full load          |                                                                  |
| M <sub>K</sub> /M <sub>N</sub> = break down torque / nominal torque     |                                           |                                                                  |

|                   |                     |                 |               |                                                                                                              |                                |
|-------------------|---------------------|-----------------|---------------|--------------------------------------------------------------------------------------------------------------|--------------------------------|
| responsible dep.  | technical reference | created by      | approved by   | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. | <a href="#">Link documents</a> |
| DI MC LVM         |                     | DT Configurator |               |                                                                                                              |                                |
|                   | document type       |                 |               |                                                                                                              | document status                |
|                   | datasheet           |                 |               |                                                                                                              | released                       |
|                   | title               |                 |               |                                                                                                              | document number                |
|                   | 1LE1503-1CB63-3AA4  |                 |               |                                                                                                              |                                |
| © Siemens AG 2023 |                     | rev.            | creation date | language                                                                                                     | Page                           |
|                   |                     | 929             | 2023-01-11    | en                                                                                                           | 1/1                            |