

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3162B

SIMOTICS SD - 160 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data Safe Area
-/-

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	9.57	-/-	19.10	1470	62.2	91.7	91.9	91.9	0.79	0.72	0.59	9.2	2.9	4.0	IE3
690	Y	50	9.57	-/-	11.10	1470	62.2	91.7	91.9	91.9	0.79	0.72	0.59	9.2	2.9	4.0	IE3
460	Δ	60	10.96	-/-	18.50	1765	59.3	92.7	92.8	92.3	0.80	0.74	0.63	9.3	3.8	4.0	IE3
460	Δ	60	11.00	-/-	18.40	1775	59.0	92.4	92.6	92.0	0.81	0.75	0.63	9.0	3.8	4.0	IE3
IM B5 / IM 3001			FS 160 M			IP55	UKCA	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						
Environmental conditions : -30 °C - +55 °C / 1000 m									Locked rotor time (hot / cold) : 26.5 s 34.3 s								
These values are calculated. The final rating plate data will be calculated when the order is placed																	
The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.																	

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 75 dB(A) ^{2) 3)}	70 / 75 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0583 kg m²		Thermal class	F
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	105 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:
I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque
1) L_{10mh} according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
SIEMENS	document type	datasheet			document status		
					released		
	title	1LE1503-1DB23-4FB4-Z			document number		
© INNOMOTICS 2023	D04+N07			rev.	creation date	language	Page
				951	2023-11-29	en	1/2

SIMOTICS SD - 160 M - IM B5 - 4p

Special design

D04	Minimum ambient temperature -30°C	N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced
-----	-----------------------------------	-----	--

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
IN LVM		SPC					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1503-1DB23-4FB4-Z						
© INNOMOTICS 2023	D04+N07						
				rev.	creation date	language	Page
				951	2023-11-29	en	2/2