

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3205B

SIMOTICS SD - 200 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
IM B3 / IM 1001		FS 200 L		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 29.4 s 45 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65 / 72 dB(A) ^{2) 3)}	67 / 74 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.2400 kg m ²		Thermal class	F
Bearing DE NDE	6212 2Z C3	6212 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	240 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(A) without (Standard)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	25 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5
Contact screw thread	M6	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal

M_K/M_N = locked rotor torque / torque nominal

M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010

2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type				document status		
	datasheet				released		
	title				document number		
	1LE1503-2AB59-0AA4						
© Siemens AG 2023	M1Y				rev.	creation date	language
					943	2023-04-06	en
						Page	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3205B

SIMOTICS SD - 200 L - IM B3 - 4p

Special design

M1Y

Non-standard winding:

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet				document status released		
	title 1LE1503-2AB59-0AA4				document number		
	M1Y				rev. 943	creation date 2023-04-06	
© Siemens AG 2023						language en	Page 2/2