

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3226B

SIMOTICS SD - 225 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
220	Δ	50	47.85	-/-	157.00	1480	308.8	95.0	95.4	95.7	0.84	0.80	0.71	7.5	3.2	3.1	IE3
380	Y	50	47.85	-/-	91.00	1480	308.8	95.0	95.4	95.7	0.84	0.80	0.71	7.5	3.2	3.1	IE3
440	Y	60	54.81	-/-	90.00	1780	294.1	94.4	94.6	94.8	0.85	0.81	0.72	7.5	3.2	3.0	IE2
440	Y	60	55.00	-/-	89.00	1782	295.0	95.4	95.7	95.4	0.85	0.82	0.73	7.4	3.1	3.0	MG1
IM B3 / IM 1001		FS 225 M		415 kg		IP55		IEC/EN 60034		IEC, EN, NEMA MG1-12							

Environmental conditions : -20 °C - +55 °C / 1,000 m

Locked rotor time (hot / cold) : 36.5 s | 55.4 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66.0 / 79.0 dB(A) ²⁾	68.0 / 82.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.6500 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5
Contact screw thread	M8	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1503-2BB62-1AA4-Z						
© Siemens AG 2021	D30+H01+L20+N07			rev.	creation date	language	Page
				01	2021-04-21 10:44	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3226B

SIMOTICS SD - 225 M - IM B3 - 4p

Special design

D30	Electrical design according to NEMA MG1-12	L20	Locating bearing, DE
H01	Bolted on mounting feet (instead of cast)	N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1503-2BB62-1AA4-Z				document number			
© Siemens AG 2021	D30+H01+L20+N07				rev. 01	creation date 2021-04-21 10:44	language en	Page 2/2