

SIMOTICS SD - 250 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	55.00	-/-	95.00	2975	177.0	94.3	94.5	93.9	0.89	0.87	0.80	6.7	2.3	3.1	IE3
690	Y	50	55.00	-/-	55.00	2975	177.0	94.3	94.5	93.9	0.89	0.87	0.80	6.7	2.3	3.1	IE3
460	Δ	60	62.00	-/-	92.00	3575	166.0	93.6	93.6	92.7	0.90	0.88	0.82	6.7	2.3	3.0	IE3
460	Δ	60	55.00	-/-	83.00	3578	147.0	93.6	93.4	92.3	0.89	0.87	0.79	7.3	2.5	3.3	IE3
IM B3 / IM 1001			FS 250 M		385 kq		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 33.7 s | 53.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73.0 / 87.0 dB(A) ²⁾	76.0 / 90.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.4600 kg m ²		Vibration severity grade	A
Bearing DE NDE	NU 215	6215 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5
Contact screw thread	M10	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1503-2CA23-4AA4-Z						
	B02+L22+Y82			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-04-23 15:27	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3252A

SIMOTICS SD - 250 M - IM B3 - 2p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Y82	Auxiliary name plate with customer data
L22	Bearing design for increased cantilever forces		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1503-2CA23-4AA4-Z			document number				
© Siemens AG 2021	B02+L22+Y82			rev. 01	creation date 2021-04-23 15:27	language en	Page 2/2	