

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3252B

SIMOTICS SD - 250 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
DOL duty (S1) - 155(F) to 130(B)																		
380	Δ	50	55.00	-/-	102.00	1482	355.0	94.6	95.1	95.0	0.87	0.84	0.76	6.8	2.5	2.9	IE3	
660	Y	50	55.00	-/-	58.00	1482	355.0	94.6	95.1	95.0	0.87	0.84	0.76	6.8	2.5	2.9	IE3	
440	Δ	60	63.00	-/-	101.00	1782	340.0	94.1	94.5	94.4	0.87	0.84	0.77	6.7	2.4	2.8	IE2	
440	Δ	60	55.00	-/-	88.00	1786	295.0	95.4	95.6	95.1	0.86	0.83	0.74	7.6	2.8	3.2	IE3	
IM B3 / IM 1001			FS 250 M				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					Grade 3	
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 34.4 s 54.1 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66 / 79 dB(A) ^{2) 3)}	68 / 82 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.8500 kg m ²		Thermal class	F
Bearing DE NDE	6215 Z C3	6215 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	420 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1503-2CB23-3AB4-Z			document number			
© Siemens AG 2022	D34			rev. 01	creation date 2022-06-17	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3252B

SIMOTICS SD - 250 M - IM B3 - 4p

Special design

D34 China Energy Efficiency Label

Notes:

responsible dep.

DI MC LVM

technical reference

created by

DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)

SIEMENS

document type

datasheet

title

1LE1503-2CB23-3AB4-Z

D34

document status

released

document number

rev.

01

creation date

2022-06-17

language

en

Page

2/2

© Siemens AG 2022