

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3252B

SIMOTICS SD - 250 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	47.85	-/-	85.00	1480	308.8	94.9	95.1	94.9	0.85	0.81	0.72	7.8	2.9	3.3	IE3
690	Y	50	47.85	-/-	49.50	1480	308.8	94.9	95.1	94.9	0.85	0.81	0.72	7.8	2.9	3.3	IE3
460	Δ	60	54.81	-/-	85.00	1780	294.1	94.3	94.5	94.3	0.85	0.81	0.73	7.7	2.8	3.2	IE2
460	Δ	60	55.00	-/-	84.00	1786	295.0	95.4	95.6	95.1	0.86	0.83	0.74	7.6	2.8	3.2	IE3
IM B3 / IM 1001		FS 250 M				IP65	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +55 °C / 1,000 m

Locked rotor time (hot / cold) : 34.9 s | 55 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66 / 79 dB(A) ^{2) 3)}	68 / 82 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.8500 kg m ²		Thermal class	F
Bearing DE NDE	6215 Z C3	6215 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	420 kg
Grease nipple	-/-		Coating (paint finish)	Special paint finish C3
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1503-2CB23-4AB4-Z				
	B02+H07+H20+N07+N31+Q02+R62				
© Siemens AG 2023		rev.	creation date	language	Page
		943	2023-04-17	en	1/2



SIMOTICS SD - 250 M - IM B3 - 4p

B02	Acceptance test certificate 3.1 acc. to EN 10204	N31	Increased air humidity/temperature with 60 to 100 g water per m3 air
H07	Stainless steel screws and bolts (outside the motor)	Q02	Anti-condensation heating for 230 V (2 terminals)
H20	IP 65 degree of protection	R62	Cast iron auxiliary terminal box (small)
N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced		

Space heaters

Technical data: 1-phase, 230 V 92W

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1503-2CB23-4AB4-Z						
	B02+H07+H20+N07+N31+Q02+R62			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-04-17	en	2/2