

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3256B

SIMOTICS SD - 250 M - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	75.00	-/-	134.00	1486	480.0	95.0	95.2	94.8	0.85	0.81	0.71	7.9	3.0	3.4	IE3
690	Y	50	75.00	-/-	78.00	1486	480.0	95.0	95.2	94.8	0.85	0.81	0.71	7.9	3.0	3.4	IE3
460	Δ	60	86.00	-/-	132.00	1785	460.0	95.4	95.6	95.3	0.86	0.82	0.73	7.8	2.9	3.3	IE3
460	Δ	60	75.00	-/-	117.00	1788	400.0	95.4	95.4	94.8	0.84	0.79	0.69	8.8	3.4	3.8	IE3
IM B5 / IM 3001			FS 250 M			IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 26.1 s 43.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70 / 83 dB(A) ²⁾	74 / 88 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	1.1000 kg m ²		Thermal class	F
Bearing DE NDE	6215 Z C3	6215 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min 50 60Hz	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	510 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1503-2CB63-4FB4				
© Siemens AG 2022		rev.	creation date	language	Page
		01	2022-02-26	en	1/1

