

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3256B

SIMOTICS SD - 250 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_f/I_N	M_A/M_N T_f/T_N	M_K/M_N T_B/T_N	IE-CL
IM B3 / IM 1001			FS 250 M		510 kg	IP55		4/4	3/4	2/4	4/4	3/4	2/4				

Environmental conditions : -20 °C - +50 °C / 1,000 m

Locked rotor time (hot / cold) : 26.1 s | 43.4 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	70.0 / 83.0 dB(A) ²⁾	74.0 / 88.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	1.1000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6215 Z C3	6215 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L_{10mh} $F_{rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
-------------------------------	---------------------	-------------------------------	-------------	--

	document type datasheet	document status released	customer	
	title 1LE1503-2CB69-0AA4-Z B02+M1Y+N06+Q02+S02+Y82	document number		
© Siemens AG 2021		rev. 01	creation date 2021-04-22 18:17	language en Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3256B

SIMOTICS SD - 250 M - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	Q02	Anti-condensation heating for 230 V (2 terminals)
M1Y	Non-standard winding:	S02	Special paint finish C3
N06	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 50°C, power reduced	Y82	Auxiliary name plate with customer data

Additional information:

Space heaters

Technical data: 1-phase, 230 V 92W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
SIEMENS	document type datasheet	document status released		customer			
	title 1LE1503-2CB69-0AA4-Z B02+M1Y+N06+Q02+S02+Y82	document number					
© Siemens AG 2021		rev. 01	creation date 2021-04-22 18:17	language en	Page 2/2		