

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3315B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	200.00	-/-	340.00	1488	1280.0	96.0	96.3	96.1	0.88	0.86	0.79	7.4	3.2	3.0	IE3
690	Y	50	200.00	-/-	198.00	1488	1280.0	96.0	96.3	96.1	0.88	0.86	0.79	7.4	3.2	3.0	IE3
460	Δ	60	230.00	-/-	345.00	1788	1230.0	95.4	95.6	95.3	0.88	0.86	0.80	7.5	3.1	2.8	IE2
460	Δ	60	200.00	-/-	300.00	1791	1070.0	96.2	96.2	95.5	0.87	0.84	0.75	8.7	3.5	3.2	IE3
IM B3 / IM 1001		FS 315 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					Grade 3	
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 25.1 s 44.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 87 dB(A) ²⁾	78 / 93 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	3.7000 kg m ²		Vibration severity grade	A
Bearing DE NDE	NU 319	6319 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} min ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
50 60Hz			Frame material	cast iron
Relubrication interval/quantity DE	40 g 40 g		Net weight of the motor (IM B3)	1190 kg
NDE	6000 h		Coating (paint finish)	Standard paint finish C2
Lubricants	Unirex N3		Color, paint shade	RAL7030
Regreasing device	Yes (standard)		Motor protection	(A) without (Standard)
Grease nipple	M10x1 DIN 3404 A		Method of cooling	IC411 - self ventilated, surface cooled
Type of bearing	Locating bearing NDE			
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5
Contact screw thread	M12	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1503-3AB53-4AA4-Z						
	D34+L22			rev.	creation date	language	Page
				01	2021-12-28	en	1/2
© Siemens AG 2021							

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3315B

SIMOTICS SD - 315 L - IM B3 - 4p

Special design

D34 China Energy Efficiency Label L22 Bearing design for increased cantilever forces

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1503-3AB53-4AA4-Z D34+L22				document number
© Siemens AG 2021		rev. 01	creation date 2021-12-28	language en	Page 2/2

