

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3315B

SIMOTICS SD - 315 L - IM V1 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	200.00	-/-	340.00	1488	1280.0	96.0	96.3	96.1	0.88	0.86	0.79	7.4	3.2	3.0	IE3
690	Y	50	200.00	-/-	198.00	1488	1280.0	96.0	96.3	96.1	0.88	0.86	0.79	7.4	3.2	3.0	IE3
460	Δ	60	230.00	-/-	345.00	1788	1230.0	95.4	95.6	95.3	0.88	0.86	0.80	7.5	3.1	2.8	IE2
460	Δ	60	200.00	-/-	300.00	1791	1070.0	96.2	96.2	95.5	0.87	0.84	0.75	8.7	3.5	3.2	IE3
IM V1 / IM 3011		FS 315 L				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 25.7 s 45.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 87 dB(A) ^{2) 3)}	78 / 93 dB(A) ^{2) 3)}	External earthing terminal	Yes (standard)
Moment of inertia	3.7000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation	20000 h	16000 h	Direction of rotation	bidirectional
50 60Hz			Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g	6000 h	Net weight of the motor (IM B3)	1190 kg
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(P) 1 resistance thermometer PT100 in stator winding - 2 wire (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1503-3AB53-4GP4-Z Q02+Q72				
© Siemens AG 2022		rev.	creation date	language	Page
		929	2022-11-15	en	1/2



SIMOTICS SD - 315 L - IM V1 - 4p

Special design

Q02	Anti-condensation heating for 230 V (2 terminals)
-----	---

Q72

2 Pt100 resistance thermometers in basic configuration for bearings (4 terminals)

Additional information:

Space heaters

Technical data:	1-phase, 230 V 109W
-----------------	---------------------

Notes:

responsible dep.

DI MC LVM

technical reference

created by

DT Configurator

approved by

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

[Link documents](#)



SIEMENS

document type

datasheet

title

1LE1503-3AB53-4GP4-Z

Q02+Q72

document status

released

document number

rev

929

creation date

2022-11-15

language

en

Page

2/2