

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3310C

SIMOTICS SD - 315 S - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	75.00	-/-	136.00	990	720.0	94.6	94.9	94.4	0.84	0.80	0.70	7.5	2.6	3.1	IE3
460	Δ	60	90.00	-/-	142.00	1190	720.0	95.0	95.3	94.8	0.84	0.81	0.72	7.2	2.6	2.9	IE3
460	Δ	60	75.00	-/-	121.00	1192	600.0	95.0	94.9	94.1	0.82	0.77	0.67	8.4	3.1	3.3	IE3
IM B3 / IM 1001		FS 315 S		750 kg		IP65	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 32.4 s 49 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63.0 / 78.0 dB(A) ²⁾	64.0 / 79.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	2.6000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(H) 3 resistance thermometers PT100 (6 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	right	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1503-3AC00-4AH5-Z						
© Siemens AG 2021	H00+H20			rev.	creation date	language	Page
				01	2021-04-20 23:07	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3310C

SIMOTICS SD - 315 S - IM B3 - 6p

Special design

H00 Canopy H20 IP 65 degree of protection

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1503-3AC00-4AH5-Z				document number			
© Siemens AG 2021	H00+H20				rev. 01	creation date 2021-04-20 23:07	language en	Page 2/2