

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3310C

SIMOTICS SD - 315 S - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
220	Δ	50	75.00	-/-	250.00	990	720.0	94.6	94.9	94.4	0.84	0.80	0.70	7.5	2.6	3.1	IE3
380	Y	50	75.00	-/-	143.00	990	720.0	94.6	94.9	94.4	0.84	0.80	0.70	7.5	2.6	3.1	IE3
IM B3 / IM 1001			FS 315 S				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1.000 m									Locked rotor time (hot / cold) : 32.5 s 49.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	72.9 / 87.3 dB(A) 2) 3)	76.7 / 91.1 dB(A) 2) 3)	External earthing terminal	Yes (standard)
Moment of inertia	2.6000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} min 50 60Hz for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	750 kg
Regreasing device	Yes (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(C) 6 PTC thermistors - for alarm and tripping (4 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC416 - separately ventilated, surface cooled

Terminal box

Terminal box position	right	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1503-3AC02-1AC5-Z F70+Q02				
© Siemens AG 2022		rev.	creation date	language	Page
		01	2022-08-10	en	1/2



SIMOTICS SD - 315 S - IM B3 - 6p

Special design

F70	Mounting of separately driven fan	Q02	Anti-condensation heating for 230 V (2 terminals)
-----	-----------------------------------	-----	---

Additional information:

Space heaters

Technical data:	1-phase, 230 V 109W
-----------------	---------------------

Notes:

[Link documents](#)

Page
2/2