

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3314C

SIMOTICS SD - 315 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
380	Δ	50	110.00	-/-	210.00	991	1060.0	95.1	95.5	95.3	0.84	0.80	0.71	7.2	2.8	3.0	IE3
660	Y	50	110.00	-/-	120.00	991	1060.0	95.1	95.5	95.3	0.84	0.80	0.71	7.2	2.8	3.0	IE3
440	Δ	60	132.00	-/-	215.00	1190	1060.0	95.0	95.4	95.3	0.85	0.82	0.74	7.0	2.7	2.8	IE2
440	Δ	60	110.00	-/-	182.00	1192	880.0	95.8	95.9	95.5	0.83	0.79	0.69	8.2	3.2	3.4	IE3

IM B3 / IM 1001		FS 315 L	990 kg	IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN		
-----------------	--	----------	--------	------	--	--------------	------------------------	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 33.7 s | 49.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63.0 / 78.0 dB(A) ²⁾	64.0 / 79.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	3.9000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(A) without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5
Contact screw thread	M12	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number	rev.	creation date
	1LE1503-3AC43-3AA4		01	2021-04-23 11:43
© Siemens AG 2021			language	Page
			en	1/1