

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3314C

SIMOTICS SD - 315 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	110.00	-/-	199.00	991	1060.0	95.1	95.5	95.3	0.84	0.80	0.71	7.2	2.8	3.0	IE3
690	Y	50	110.00	-/-	115.00	991	1060.0	95.1	95.5	95.3	0.84	0.80	0.71	7.2	2.8	3.0	IE3
IM B3 / IM 1001			FS 315 L			IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN						Grade 3	
Environmental conditions : -20 °C - +40 °C / 1.000 m									Locked rotor time (hot / cold) : 33.9 s 50.3 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	72.9 / 87.3 dB(A) 2) 3)	76.7 / 91.1 dB(A) 2) 3)	External earthing terminal	Yes (standard)
Moment of inertia	3.9000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
50 60Hz			Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g	6000 h	Net weight of the motor (IM B3)	990 kg
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Type of bearing	Locating bearing DE		Method of cooling	IC416 - separately ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE1503-3AC43-4AF4-Z				
	B60+B61+D34+F70+G06+L51+R62+Y56+Y82+Y84				
© Siemens AG 2022		rev.	creation date	language	Page
		929	2022-09-28	en	1/2



Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3314C

SIMOTICS SD - 315 L - IM B3 - 6p

Special design

B60	Document electrical datasheet	L51	Bearing insulation NDE
B61	Document order dimension drawing	R62	Cast iron auxiliary terminal box (small)
D34	China Energy Efficiency Label	Y56	Paint finish in special RAL colours
F70	Mounting of separately driven fan	Y82	Auxiliary name plate with customer data
G06	Mounting a rotary pulse encoder HOG 10 D 1024 I	Y84	Additional data on the rating plate and on the packing label :

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1503-3AC43-4AF4-Z B60+B61+D34+F70+G06+L51+R62+Y56+Y82+Y84				document number
© Siemens AG 2022		rev. 929	creation date 2022-09-28	language en	Page 2/2

