

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4104B

SIMOTICS SD - 100 L - IM B34 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	2.20	-/-	4.50	1465	14.3	89.5	89.6	88.3	0.79	0.73	0.61	8.5	3.3	4.7	IE4
690	Y	50	2.20	-/-	2.60	1465	14.3	89.5	89.6	88.3	0.79	0.73	0.61	8.5	3.3	4.7	IE4
460	Δ	60	2.55	-/-	4.40	1765	13.8	91.0	91.0	89.7	0.80	0.74	0.63	8.9	3.3	4.7	IE4
460	Δ	60	2.20	-/-	3.90	1770	11.9	91.0	90.6	88.7	0.77	0.70	0.58	9.9	3.9	5.5	IE4
IM B34 / IM 2101		FS 100 L				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 21.8 s 26 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63 / 75 dB(A) ^{2) 3)}	66 / 78 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0140 kg m ²		Thermal class	F
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	41 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F01	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411

M_K/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

M_B/M_N = break down torque / nominal torque

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
DI MC LVM		DT Configurator						
	document type				document status			
	datasheet				released			
	title				document number			
	1LE1504-1AB43-4NA4-Z							
© Siemens AG 2023	H01+P01				rev.	creation date	language	Page
					943	2023-04-27	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4104B

SIMOTICS SD - 100 L - IM B34 - 4p

Special design

H01 Bolted on mounting feet (instead of cast) P01 Next larger standard flange

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1504-1AB43-4NA4-Z			document number			
© Siemens AG 2023	H01+P01			rev. 943	creation date 2023-04-27	language en	Page 2/2

