

SIMOTICS SD - 160 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
400	Δ	50	15.00	-/-	26.00	2955	48.5	93.3	93.5	92.9	0.90	0.87	0.80	9.0	3.1	4.5	IE4
690	Y	50	15.00	-/-	14.90	2955	48.5	93.3	93.5	92.9	0.90	0.87	0.80	9.0	3.1	4.5	IE4
460	Δ	60	17.30	-/-	26.00	3555	46.5	93.0	93.0	92.1	0.90	0.88	0.81	8.8	3.0	4.3	IE4
460	Δ	60	15.00	-/-	23.00	3560	40.0	92.4	92.1	90.9	0.89	0.86	0.78	10.0	3.5	5.0	IE4

IM B3 / IM 1001	FS 160 M	130 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	----------	--------	------	--------------	------------------------

Locked rotor time (hot / cold) : 25.3 s | 32.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	74.0 / 87.0 dB(A) ²⁾	79.0 / 92.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0680 kg m²		Vibration severity grade	A
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs


Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

	document type	document status		customer	
	datasheet	released			
	title	document number			
	1LE1504-1DA33-4AB4				
© Siemens AG 2021		rev.	creation date	language	Page
		01	2021-04-22 13:18	en	1/1