

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4164B

SIMOTICS SD - 160 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	15.00	-/-	29.00	1480	97.0	93.9	94.0	93.3	0.80	0.74	0.62	7.8	3.7	4.3	IE4
690	Y	50	15.00	-/-	16.70	1480	97.0	93.9	94.0	93.3	0.80	0.74	0.62	7.8	3.7	4.3	IE4
460	Δ	60	17.30	-/-	28.50	1780	93.0	94.5	94.6	94.0	0.81	0.76	0.64	7.9	3.4	4.2	IE4
460	Δ	60	15.00	-/-	25.50	1780	80.0	94.1	94.0	93.0	0.79	0.72	0.60	8.8	3.9	4.8	IE4
IM B5 / IM 3001		FS 160 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 33.1 s 43.6 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63 / 76 dB(A) ²⁾	66 / 79 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0990 kg m ²		Thermal class	F
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min ¹⁾ for coupling operation	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	138 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet			document status released	
	title 1LE1504-1DB43-4FA4-Z B02+Y82			document number	
© Siemens AG 2022			rev. 01	creation date 2022-02-01	language en
					Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4164B

SIMOTICS SD - 160 L - IM B5 - 4p

Special design

B02 Acceptance test certificate 3.1 acc. to EN 10204 Y82 Auxiliary name plate with customer data

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1504-1DB43-4FA4-Z B02+Y82				document number
© Siemens AG 2022		rev. 01	creation date 2022-02-01	language en	Page 2/2

