

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4164B

SIMOTICS SD - 160 L - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	15.00	-/-	29.00	1480	97.0	93.9	94.0	93.3	0.80	0.74	0.62	7.8	3.7	4.3	IE4
690	Y	50	15.00	-/-	16.70	1480	97.0	93.9	94.0	93.3	0.80	0.74	0.62	7.8	3.7	4.3	IE4
460	Δ	60	17.30	-/-	28.50	1780	93.0	94.5	94.6	94.0	0.81	0.76	0.64	7.9	3.4	4.2	IE4
460	Δ	60	15.00	-/-	25.50	1780	80.0	94.1	94.0	93.0	0.79	0.72	0.60	8.8	3.9	4.8	IE4
IM B35 / IM 2001		FS 160 L				IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 33.1 s 43.6 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63 / 76 dB(A) ²⁾	66 / 79 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0990 kg m ²		Thermal class	F
Bearing DE NDE	6209 2Z C3	6209 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad} min ¹⁾ for coupling operation	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	138 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411

M_A/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

M_K/M_N = break down torque / nominal torque

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
DI MC LVM		DT Configurator						
	document type	datasheet			document status			
					released			
	title	1LE1504-1DB43-4JA4-Z			document number			
© Siemens AG 2022	B02+Y82				rev.	creation date	language	Page
					01	2022-03-15	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4164B

SIMOTICS SD - 160 L - IM B35 - 4p

Special design

B02 Acceptance test certificate 3.1 acc. to EN 10204 Y82 Auxiliary name plate with customer data

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet				document status released		
	title 1LE1504-1DB43-4JA4-Z				document number		
© Siemens AG 2022	B02+Y82	rev. 01		creation date 2022-03-15		language en	