

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4184B

SIMOTICS SD - 180 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	60	25.30	-/-	82.00	1775	136.0	94.5	94.8	94.6	0.82	0.77	0.67	7.8	2.8	3.7	IE4
400	Y	60	25.30	-/-	47.00	1775	136.0	94.5	94.8	94.6	0.82	0.77	0.67	7.8	2.8	3.7	IE4
230	Δ	60	22.00	-/-	74.00	1778	118.0	94.5	94.6	94.0	0.79	0.73	0.61	8.9	3.1	4.3	IE4
400	Y	60	22.00	-/-	42.50	1778	118.0	94.5	94.6	94.0	0.79	0.73	0.61	8.9	3.1	4.3	IE4
IM B3 / IM 1001		FS 180 L		192 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 34.5 s 47.8 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	62.0 / 75.0 dB(A) ²⁾	76.0 / 87.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.1800 kg m ²		Vibration severity grade	A
Bearing DE NDE	6210 Z C3	6210 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
SIEMENS	document type datasheet			document status released		customer	
	title 1LE1504-1EB41-8AA4			document number			
© Siemens AG 2021			rev. 01	creation date 2021-04-22 09:53		language en	Page 1/1