

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4205B

SIMOTICS SD - 200 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
380	Δ	50	30.00	-/-	59.00	1475	194.0	94.9	95.2	94.9	0.81	0.76	0.65	7.3	3.2	3.6	IE4
660	Y	50	30.00	-/-	34.00	1475	194.0	94.9	95.2	94.9	0.81	0.76	0.65	7.3	3.2	3.6	IE4
440	Δ	60	34.50	-/-	58.00	1775	186.0	95.4	95.6	95.3	0.82	0.77	0.67	7.5	3.0	3.5	IE4
440	Δ	60	30.00	-/-	52.00	1780	161.0	95.0	95.0	94.3	0.80	0.74	0.63	8.4	3.5	4.0	IE4

IM B3 / IM 1001		FS 200 L	258 kg	IP65		IEC/EN 60034	IEC, DIN, ISO, VDE, EN						
-----------------	--	----------	--------	------	--	--------------	------------------------	--	--	--	--	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 47.8 s | 66.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	59.0 / 72.0 dB(A) ²⁾	62.0 / 75.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.2700 kg m ²		Vibration severity grade	A
Bearing DE NDE	6212 Z C3	6212 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Special paint finish C3
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	25.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1504-2AB53-3AB4-Z			
	B02+H20+S02			
© Siemens AG 2021		rev.	creation date	language Page
		01	2021-04-22 12:57	en 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4205B

SIMOTICS SD - 200 L - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	S02	Special paint finish C3
H20	IP 65 degree of protection		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1504-2AB53-3AB4-Z			document number				
© Siemens AG 2021	B02+H20+S02			rev. 01	creation date 2021-04-22 12:57	language en	Page 2/2	