

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4205B

SIMOTICS SD - 200 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{3)}$			$\cos\phi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I_l/I_N	T_l/T_N	T_B/T_N	
400	Δ	50	30.00	-/-	56.00	1475	194.0	94.9	95.2	94.9	0.81	0.76	0.65	7.3	3.2	3.6	IE4
690	Y	50	30.00	-/-	32.50	1475	194.0	94.9	95.2	94.9	0.81	0.76	0.65	7.3	3.2	3.6	IE4
460	Δ	60	34.50	-/-	55.00	1775	186.0	95.4	95.6	95.3	0.82	0.77	0.67	7.5	3.0	3.5	IE4
460	Δ	60	30.00	-/-	49.50	1780	161.0	95.0	95.0	94.3	0.80	0.74	0.63	8.4	3.5	4.0	IE4

IM B5 / IM 3001		FS 200 L	258 kg	IP55		IEC/EN 60034	IEC, DIN, ISO, VDE, EN		
-----------------	--	----------	--------	------	--	--------------	------------------------	--	--

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 47.8 s | 66.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	59.0 / 72.0 dB(A) ²⁾	62.0 / 75.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.2700 kg m ²		Vibration severity grade	A
Bearing DE NDE	6212 Z C3	6212 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	25.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5
Contact screw thread	M6	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1504-2AB53-4FA4			
© Siemens AG 2021		rev.	creation date	language
		01	2021-04-21 13:49	en
				Page
				1/1