

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4222A

SIMOTICS SD - 225 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
380	Δ	50	45.00	-/-	85.00	2970	145.0	95.0	95.0	94.4	0.85	0.81	0.71	8.8	3.1	4.1	IE4
660	Y	50	45.00	-/-	48.50	2970	145.0	95.0	95.0	94.4	0.85	0.81	0.71	8.8	3.1	4.1	IE4
440	Δ	60	51.00	-/-	81.00	3570	136.0	94.5	94.4	93.6	0.87	0.83	0.74	8.7	3.1	4.0	IE4
440	Δ	60	45.00	-/-	74.00	3575	120.0	94.5	94.3	93.3	0.85	0.80	0.70	9.8	3.5	4.6	IE4
IM B3 / IM 1001		FS 225 M		330 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 32.5 s | 49.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75.0 / 86.0 dB(A) ²⁾	76.0 / 87.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.2600 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 C3	6213 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	20 g 20 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish, resistant to salt-laden air C4
Regreasing device	with regreasing nipple		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 71412 A		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	left	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status	customer		
	datasheet			released			
	title			document number			
	1LE1504-2BA23-3AB6-Z						
	B02+F76+L19+S03						
© Siemens AG 2021		rev.	creation date	language	Page		
		01	2021-04-21 18:23	en			

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4222A

SIMOTICS SD - 225 M - IM B3 - 2p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A
F76	Metal external fan	S03	Special paint finish in sea air resistant C4

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1504-2BA23-3AB6-Z				document number			
© Siemens AG 2021	B02+F76+L19+S03				rev. 01	creation date 2021-04-21 18:23	language en	Page 2/2