

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4220B

SIMOTICS SD - 225 S - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
220	Δ	60	37.00	-/-	123.00	1786	198.0	95.4	95.4	94.8	0.83	0.78	0.68	9.8	3.6	3.6	IE4	
380	Y	60	37.00	-/-	71.00	1786	198.0	95.4	95.4	94.8	0.83	0.78	0.68	9.8	3.6	3.6	IE4	
IM B3 / IM 1001			FS 225 S		345 kg		IP55			IEC/EN 60034		IEC, DIN, ISO, VDE, EN						
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 35.2 s 46.8 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 82 dB(A) ²⁾	69 / 81 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.5200 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6213 Z C3	6213 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	345 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5
Contact screw thread	M8	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque
1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1504-2BB09-0AA4-Z		document number			
© Siemens AG 2021		B02+B60+M2A		rev.	creation date	language	Page
				01	2021-09-03 09:40	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4220B

SIMOTICS SD - 225 S - IM B3 - 4p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	M2A	220 VD/380 VY; 60Hz, 50-Hz power
B60	Document electrical datasheet		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1504-2BB09-0AA4-Z B02+B60+M2A							document number
© Siemens AG 2021		rev. 01	creation date 2021-09-03 09:40		language en	Page 2/2		