

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4222B

SIMOTICS SD - 225 M - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 155(F)																	
400	Δ	50	45.00	-/-	81.00	1485	290.0	95.4	95.7	95.4	0.84	0.80	0.70	8.0	3.4	3.3	IE4
690	Y	50	45.00	-/-	47.00	1485	290.0	95.4	95.7	95.4	0.84	0.80	0.70	8.0	3.4	3.3	IE4
460	Δ	60	52.00	-/-	80.00	1785	280.0	95.4	95.6	95.2	0.85	0.81	0.72	8.2	3.2	3.2	IE3
460	Δ	60	45.00	-/-	71.00	1786	240.0	95.4	95.4	94.7	0.83	0.78	0.67	9.3	3.9	3.7	IE4
IM B35 / IM 2001		SF: 1.15	FS 225 M				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 40.4 s 54.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64 / 79 dB(A) ^{2) 3)}	68 / 81 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.6600 kg m ²		Thermal class	F
Bearing DE NDE	6213 Z C3	6213 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	No		Net weight of the motor (IM B3)	415 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	Yes (standard)		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M8	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal

M_K/M_N = locked rotor torque / torque nominal

M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010

2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type	datasheet			document status		
					released		
	title	1LE1504-2BB23-4JB4-Z			document number		
	F74+F76+L02+N01						
© Siemens AG 2023		rev.	creation date	language	Page		
		929	2023-01-13	en	1/2		

SIMOTICS SD - 225 M - IM B35 - 4p

F74	Sheet steel fan cowl	L02	Full-key balancing
F76	Metal external fan	N01	Temperature class 155 (F), utilised to 155 (F), with service factor (SF)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1504-2BB23-4JB4-Z			document number			
© Siemens AG 2023	F74+F76+L02+N01			rev. 929	creation date 2023-01-13	language en	Page 2/2