

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4282B

SIMOTICS SD - 280 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data	Safe Area -/-
-----------------	------------------

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	90.00	-/-	157.00	1488	580.0	96.1	96.3	96.1	0.86	0.82	0.73	9.0	3.2	3.4	IE4
690	Y	50	90.00	-/-	91.00	1488	580.0	96.1	96.3	96.1	0.86	0.82	0.73	9.0	3.2	3.4	IE4
460	Δ	60	104.00	-/-	158.00	1790	550.0	96.2	96.2	95.6	0.86	0.82	0.72	9.0	3.2	3.4	IE4
460	Δ	60	90.00	-/-	137.00	1788	480.0	96.2	96.3	95.8	0.86	0.82	0.74	9.5	3.5	3.7	IE4
IM B3 / IM 1001		FS 280 M				IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 29 s 40.9 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 83 dB(A) ^{2) 3)}	74 / 88 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	2.0000 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	730 kg
Regreasing device	With (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5
Contact screw thread	M10	Cable gland	2 plugs

Notes:			
I _A /I _N = locked rotor current / current nominal		1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal		2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque			

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1504-2DB23-4AA4			document number			
© INNOMOTICS 2023				rev. 950	creation date 2023-09-30	language en	Page 1/1