

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2073D

SIMOTICS SD - 71 M - IM B5 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data	Safe Area -/-
-----------------	------------------

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	0.12	-/-	1.15	640	1.8	39.8	39.3	34.5	0.66	0.55	0.44	1.8	1.8	1.8	IE2
400	Y	50	0.12	-/-	0.66	640	1.8	39.8	39.3	34.5	0.66	0.55	0.44	1.8	1.8	1.8	IE2
460	Y	60	0.14	-/-	0.69	795	1.7	40.0	39.0	34.6	0.64	0.54	0.43	2.1	1.9	2.0	IE2
460	Y	60	0.12	0.16	0.66	815	1.4	40.0	38.0	33.0	0.57	0.49	0.39	2.1	2.3	2.4	MG1
IM B5 / IM 3001		FS 71 M				IP55	UKCA	IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12				kVA Code:			
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 108.7 s 138.8 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A) ^{2) 3)}	/ dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0010 kg m ²		Thermal class	F
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 D11	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:			
I _A /I _N = locked rotor current / current nominal		1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal		2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque			

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
IN LVM		SPC			
SIEMENS	document type			document status	
	datasheet			released	
	title			document number	
	1LE1521-0CD32-2FA4				
© INNOMOTICS 2023	rev.		creation date		language
	950		2023-10-31		Page
				en	1/1