

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3104B

SIMOTICS SD - 100 L - IM B5 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
230	Δ	50	2.20	-/-	7.70	1465	14.3	86.7	87.0	85.9	0.83	0.77	0.66	8.4	3.2	4.4	IE3
400	Y	50	2.20	-/-	4.40	1465	14.3	86.7	87.0	85.9	0.83	0.77	0.66	8.4	3.2	4.4	IE3
460	Y	60	2.54	-/-	4.25	1765	13.8	89.5	89.7	88.5	0.84	0.81	0.69	8.5	3.0	4.4	IE3
460	Y	60	2.20	3.00	3.85	1770	11.9	89.5	89.2	87.2	0.81	0.75	0.63	9.6	3.5	5.1	MG1
IM B5 / IM 3001		FS 100 L		40 kg		IP55	CC032A	IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12-12				kVA Code: N			

Environmental conditions : -20 °C - + °C / 1,000 m

Locked rotor time (hot / cold) : 19 s | 22.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60.0 / 72.0 dB(A) ²⁾	62.0 / 74.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0140 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F01	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1523-1AB42-2FA4-Z						
	F74+N03			rev.	creation date	language	Page
© Siemens AG 2021				01	2021-05-24 17:40	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3104B

SIMOTICS SD - 100 L - IM B5 - 4p

Special design

F74	Sheet steel fan cowl	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature
-----	----------------------	-----	---

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet				document status released		customer	
	title 1LE1523-1AB42-2FA4-Z				document number			
© Siemens AG 2021	F74+N03				rev. 01	creation date 2021-05-24 17:40	language en	Page 2/2