

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3204A

SIMOTICS SD - 200 L - IM V1 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N		
415	Δ	50	30.00	-/-	51.00	2955	97.0	93.3	93.6	93.3	0.87	0.83	0.75	7.0	2.5	3.3	IE3	
480	Δ	60	33.50	-/-	50.00	3555	90.0	93.0	93.1	92.6	0.87	0.84	0.77	7.1	2.5	3.3	IE3	
480	Δ	60	30.00	40.00	44.50	3560	80.0	92.4	92.2	91.4	0.87	0.83	0.74	7.6	2.9	3.6	MG1	
IM V1 / IM 3011			FS 200 L		225 kg		IP55	CC032A		IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12-12			kVA Code: J			
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 34.1 s 52.3 s									

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 80 dB(A) ²⁾	78 / 86 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.1340 kg m ²		Vibration severity grade	A
Bearing DE NDE	6212 Z C3	6212 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} , F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	25 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
¹⁾ L10mh according to DIN ISO 281 10/2010
²⁾ at rated power / at full load
³⁾ Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1523-2AA43-5GA4-Z			document number				
© Siemens AG 2021	Q03			rev. 01	creation date 2021-07-26 09:57	language en	Page 1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3204A

SIMOTICS SD - 200 L - IM V1 - 2p

Special design

Q03 Anti-condensation heating 115 V

Additional information:

Space heaters

Technical data: 1-phase, 115 V 50W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet			document status released		customer		
	title 1LE1523-2AA43-5GA4-Z			document number				
© Siemens AG 2021	Q03			rev. 01	creation date 2021-07-26 09:57	language en	Page 2/2	