

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3252B

SIMOTICS SD - 250 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	55.00	-/-	96.00	1482	355.0	94.6	95.1	95.0	0.87	0.84	0.76	6.8	2.5	2.9	IE3
460	Δ	60	63.00	-/-	97.00	1782	340.0	94.1	94.5	94.4	0.87	0.84	0.77	6.7	2.4	2.8	IE2
460	Δ	60	55.00	75.00	84.00	1786	295.0	95.4	95.6	95.1	0.86	0.83	0.74	7.6	2.8	3.2	MG1
IM B3 / IM 1001		FS 250 M		420 kg		IP55	CC032A	IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12-12				kVA Code: J			

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 34.4 s | 54.1 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	66.0 / 79.0 dB(A) ²⁾	68.0 / 82.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.8500 kg m ²		Vibration severity grade	A
Bearing DE NDE	6215 Z C3	6215 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5
Contact screw thread	M10	Cable gland	2 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _K /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _B /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type			document status		customer	
	datasheet			released			
	title			document number			
	1LE1523-2CB23-4AA4						
© Siemens AG 2021			rev.	creation date		language	Page
			01	2021-04-21 23:18		en	1/1