

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2182A

SIMOTICS SD - 180 M - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
220	Δ	50	22.00	-/-	73.00	2940	71.0	91.3	91.6	90.9	0.87	0.83	0.74	7.4	2.7	3.6	IE2
380	Y	50	22.00	-/-	42.00	2940	71.0	91.3	91.6	90.9	0.87	0.83	0.74	7.4	2.7	3.6	IE2
440	Y	60	24.50	-/-	40.50	3540	66.0	91.0	91.0	89.9	0.87	0.83	0.74	7.7	2.8	3.8	IE2
440	Y	60	22.00	-/-	37.00	3550	59.0	91.0	90.8	89.5	0.86	0.81	0.72	8.4	3.0	4.1	IE2
IM B5 / IM 3001		FS 180 M		145 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN				KS C IEC60034-2-1			

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 13.1 s | 23.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	77.0 / 84.0 dB(A) ²⁾	80.0 / 87.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.0690 kg m ²		Vibration severity grade	A
Bearing DE NDE	6210 Z C3	6210 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_K/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1541-1EA22-1FA4		document number			
© Siemens AG 2021				rev.	creation date	language	Page
				01	2021-04-23 11:45	en	1/1