

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2282C

SIMOTICS SD - 280 M - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
400	Δ	60	57.42	-/-	105.00	1185	462.8	93.5	93.9	94.1	0.84	0.80	0.72	7.1	2.9	2.8	IE1
690	Y	60	57.42	-/-	61.00	1185	462.8	93.5	93.9	94.1	0.84	0.80	0.72	7.1	2.9	2.8	IE1
IM B3 / IM 1001			FS 280 M		510 kg	IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN				KS C IEC60034-2-1			

Environmental conditions : -20 °C - +55 °C / 1,000 m

Locked rotor time (hot / cold) : 15.4 s | 25 s

These values are calculated. The final rating plate data will be calculated when the order is placed

The efficiency values and efficiency class according to EuP directive are valid for standard power ratings under standard conditions.

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 79.0 dB(A) ²⁾	67.0 / 81.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	1.3700 kg m ²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g	4000 h	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 3404 A		Motor protection	(A) without (Standard)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	120.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5
Contact screw thread	M10	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
DI MC LVM		DT Configurator		

	document type	document status	customer	
	datasheet	released		
	title	document number		
	1LE1541-2DC29-0AA4-Z			
	M1J+N07			
© Siemens AG 2021		rev.	creation date	language Page
		01	2021-04-23 08:33	en 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2282C

SIMOTICS SD - 280 M - IM B3 - 6p

Special design

M1J	400 VD/690 VY, 60-Hz power	N07	Temperature class 155 (F), utilised to 130 (B), cooling medium temperature 55°C, power reduced
-----	----------------------------	-----	--

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
-------------------------------	---------------------	-------------------------------	-------------	--

	document type datasheet	document status released		customer	
	title 1LE1541-2DC29-0AA4-Z M1J+N07	document number			
© Siemens AG 2021		rev. 01	creation date 2021-04-23 08:33	language en	Page 2/2