

SIMOTICS SD - 280 M - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	55.00	-/-	99.00	988	530.0	94.1	94.5	94.4	0.85	0.81	0.73	7.2	3.3	3.0	IE3
460	Δ	60	66.00	-/-	102.00	1186	530.0	94.1	94.6	94.4	0.86	0.83	0.76	7.8	3.0	2.7	IE2
460	Δ	60	55.00	-/-	87.00	1190	440.0	94.5	94.6	93.9	0.84	0.80	0.70	9.2	3.6	3.3	IE3
IM B3 / IM 1001			FS 280 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN						KS C IEC60034-2-	

Locked rotor time (hot / cold) : 22 s | 30.6 s

Sound level (SPL / SWL) at 50Hz 60Hz	60 / 74 dB(A) ^{2) 3)}	66 / 80 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	1.6400 kg m²		Vibration severity grade	A
Bearing DE NDE	6317 C3	6317 C3	Thermal class	F
bearing lifetime			Duty type	S1
L10mh F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	30 g 30 g 8000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	560 kg
Regreasing device	With (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Bearing insulation DE / Bearing insulation NDE	Yes (non-drive end)		Method of cooling	IC416 - separately ventilated, surface cooled
Condensate drainage holes	With (standard)			

Terminal box position	top	Max. cross-sectional area	120 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1543-2DC23-4AF4-Z D33+F70+G05+L51			document number			
© Siemens AG 2023				rev. 943	creation date 2023-05-26	language en	Page 1/2

SIMOTICS SD - 280 M - IM B3 - 6p

D33	KEA Korea Energy Efficiency Label	G05	Mounting a rotary pulse encoder HOG 9 D 1024 I
F70	Mounting of separately driven fan	L51	Bearing insulation NDE

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1543-2DC23-4AF4-Z						
© Siemens AG 2023	D33+F70+G05+L51			rev.	creation date	language	Page
				943	2023-05-26	en	2/2