

SIMOTICS SD Premium Insulation - 250 M - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	30.00	-/-	61.00	734	390.0	91.3	92.0	91.8	0.78	0.71	0.59	6.4	2.5	2.9	IE3
690	Y	50	30.00	-/-	35.00	734	390.0	91.3	92.0	91.8	0.78	0.71	0.59	6.4	2.5	2.9	IE3
460	Δ	60	36.00	-/-	62.00	882	390.0	91.7	92.4	92.4	0.80	0.70	0.59	6.3	2.3	2.7	IE2
460	Δ	60	30.00	-/-	54.00	886	325.0	91.7	92.0	91.4	0.76	0.69	0.56	7.3	2.8	3.3	IE3
IM B3 / IM 1001			FS 250 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN				KS C IEC60034-2-			

Locked rotor time (hot / cold) : 16.4 s | 26.3 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	60 / 74 dB(A) ^{2) 3)}	65 / 79 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.8510 kg m²		Thermal class	F
Bearing DE NDE	6315 Z C3	6315 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	370 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing NDE		Color, paint shade	RAL7030
Condensate drainage holes	With (standard)		Motor protection	(A) without (Standard)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	120 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 42 mm
Type of terminal box	TB1 N01	Cable entry	2xM63x1,5
Contact screw thread	M10	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1583-2CD23-4AA4-Z			document number			
© Siemens AG 2023	L25			rev. 943	creation date 2023-05-29	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3252D

SIMOTICS SD Premium Insulation - 250 M - IM B3 - 8p

Special design

L25 Double sides reinforced bearings for DE and NDE, Type 63

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
	document type datasheet				document status released
	title 1LE1583-2CD23-4AA4-Z L25				document number
© Siemens AG 2023				rev. 943	creation date 2023-05-29
				language en	Page 2/2

