

SIMOTICS SD Premium Insulation - 315 L - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	132.00	-/-	255.00	741	1700.0	94.0	94.6	94.8	0.79	0.75	0.64	8.0	3.0	3.3	IE3
690	Y	50	132.00	-/-	149.00	741	1700.0	94.0	94.6	94.8	0.79	0.75	0.64	8.0	3.0	3.3	IE3
460	Δ	60	158.00	-/-	260.00	890	1700.0	94.5	95.1	95.3	0.81	0.77	0.67	7.7	2.8	3.1	IE3
460	Δ	60	132.00	-/-	220.00	893	1410.0	94.5	94.9	94.7	0.80	0.75	0.64	9.0	3.2	3.8	IE3
IM B3 / IM 1001			FS 315 L			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN				KS C IEC60034-2-1			
Environmental conditions : -20 °C - +40 °C / 1,000 m									Locked rotor time (hot / cold) : 14.6 s 24.5 s								

Sound level (SPL / SWL) at 50Hz 60Hz	76 / 90 dB(A) ^{2) 3)}	81 / 95 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	5.5100 kg m ²		Vibration severity grade	A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	1250 kg
Regreasing device	With (standard)		Coating (paint finish)	Standard paint finish C2
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	240 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1 Q01	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M12	Cable gland	4 plugs

Notes:

I_r/I_n = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_n = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_n = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1583-3AD63-4AB4-Z			document number			
© Siemens AG 2023	D47+Q02			rev. 943	creation date 2023-03-28	language en	Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3316D

SIMOTICS SD Premium Insulation - 315 L - IM B3 - 8p

Special design

D47

TR CU product safety certificate EAC for the Eurasian Customs Union

Q02

Anti-condensation heating for 230 V (2 terminals)

Additional information:

Space heaters

Technical data:

1-phase, 230 V 109W

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1583-3AD63-4AB4-Z			document number			
	D47+Q02			rev. 943	creation date 2023-03-28		
© Siemens AG 2023						language en	Page 2/2