

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2163D

SIMOTICS SD - 160 M - IM B3 - 8p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
400	Δ	50	5.50	-/-	14.10	730	72.0	83.8	84.2	83.0	0.67	0.60	0.49	3.9	1.7	2.0	IE2
690	Y	50	5.50	-/-	8.20	730	72.0	83.8	84.2	83.0	0.67	0.60	0.49	3.9	1.7	2.0	IE2
460	Δ	60	6.30	-/-	13.80	880	68.0	85.5	86.0	85.0	0.67	0.61	0.51	4.0	1.7	2.0	IE2
460	Δ	60	5.50	-/-	12.40	885	59.0	85.5	85.6	84.0	0.65	0.59	0.48	4.4	2.0	2.3	IE2
IM B3 / IM 1001		FS 160 M		111 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 59.8 s | 85.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63.0 / 75.0 dB(A) ²⁾	71.0 / 83.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0830 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 Z C3	6309 Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	-/-		Motor protection	(F) 1 temperature sensor KTY84-130 (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	2 glands, 1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
DI MC LVM		DT Configurator					
	document type	datasheet		document status	released		
	title	1LE1601-1DD33-4AF4-Z		document number			
© Siemens AG 2021	D22+D47+G04+G43+Q01+R16		rev.	creation date	language	Page	
			01	2021-04-23 16:26	en	1/2	

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2163D

SIMOTICS SD - 160 M - IM B3 - 8p

Special design

D22	motor without CE character for export outside the EEA (see EU regulation 640/2009)	G43	Mechanical protection for encoder
D47	TR CU product safety certificate EAC for the Eurasian Customs Union	Q01	Measuring nipple for SPM shock pulse measurement to monitor bearings
G04	Mounted rotary pulse encoder LL 861 900 220	R16	EMC cable gland, maximum number

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.			
	document type datasheet	document status released			customer			
	title 1LE1601-1DD33-4AF4-Z							
© Siemens AG 2021	D22+D47+G04+G43+Q01+R16	rev. 01	creation date 2021-04-23 16:26		language en	Page 2/2		